

## Pure Supreme™ (Tentative) LINER

Production Unit: Gruvön

### Product Description

Pure Supreme™ is a fully coated premium white top kraftliner suitable for offset printing and litho-laminated packaging. High strength ensures light, strong packages with minimised washboarding.

Pure Supreme™ is produced from 100% virgin fibres.

### Grammages

36, 41 lb/1000ft<sup>2</sup>

175, 200 g/m<sup>2</sup>

### Approvals

Pure Supreme™ is produced in compliance with FDA and BfR packaging norms.

### Certification

Gruvön mill is certified in accordance with ISO 9001 ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit				Method
Grammage	lb/1000ft <sup>2</sup>		36	41	ISO 536
Caliper	in/1000		8,7	10,2	ISO 534
Scott Bond	lbf/in		1,1	1,1	TAPPI T569
SCT	lbf/in	MD	31	37	ISO 9895
	lbf/in	CD	22	27	
Tensile stiffness	lbf/in	MD	7990	9130	ISO 1924
	lbf/in	CD	4110	4900	
Bending Force	lbf	MD	0,020	0,027	ISO 2493
	lbf	CD	0,007	0,011	
Roughness PPS-10	Microns	PS	1,5	1,5	ISO 8791-4
Gloss	%	PS	45	45	ISO 8254-1
Brightness	%	PS	80	80	ISO 2470
Whiteness D65	%	PS	84	84	ISO 11475
Cobb 60	lb/1000ft <sup>2</sup>	PS	7,4	7,4	ISO 535
	lb/1000ft <sup>2</sup>	RS	8,2	8,2	
Moisture	%		7,0	7,0	ISO 287

MD = Machine Direction

CD = Cross Direction

PS = Printing Side

RS = Reverse Side

Test climate: 50% RH, 23C

The table shows typical values for a range of products